

Sequential thermostatic shower mixer

Ref. H9640

Thermostatic mixer with no non-return valves, top outlet



DESCRIPTION

Sequential thermostatic shower mixer - Ref. H9640

SECURITHERM thermostatic sequential shower mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between the hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior (reduces niches where bacteria can develop).
Flow rate regulated at 9 lpm.
Chrome-plated brass body and Hygiene lever L. 100mm.
M3/4" top shower outlet.
Wall-mounted mixer with offset STOP/CHECK connectors, M1/2" M3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.


ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H9640

Connector	3/4"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Width	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass



Norms



Warranty

