TEMPOMIX 3 time flow mixer

Ref. 794000

Soft-touch operation, stopcocks



ADVANTAGES



Exceptional water savings: 85%




Soft-touch operation



Sleek lines





TEMPOMIX 3 time flow mixer - Ref. 794000

Deck-mounted single control time flow basin mixer:

Soft-touch operation.

DESCRIPTION

Temperature control and operation on the push-button.

Time flow pre-set at ~7 seconds.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Tamperproof scale-resistant flow straightener.

Chrome-plated metal body.

PEX flexibles F3/8" with stopcocks, filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Adjustable maximum temperature limiter.


Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 794000

Connector	F3/8"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS BELGAGUA COMPANY SWEAT STATES
Warranty	30 S WASRANTY
Repairability	50 g



© DELABIE https://www.delabie.com