TEMPOMIX 3 time flow mixer

Ref. 794100

Soft-touch operation



DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 794100

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow pre-set at ~7 seconds, adjustable from 6 to 9 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated brass body.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 85%
- Soft-touch operation
- Sleek lines
- Sleek design

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 794100

Connector	F3/8"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	ACS, BELGAQUA, WRAS, kiwa, DVGW
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

