# TEMPOMIX 3 time flow mixer

Ref. 794100

Soft-touch operation



## DESCRIPTION

**TEMPOMIX 3 time flow mixer** - Ref. 794100

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow pre-set at ~7 seconds, adjustable from 6 to 9 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated brass body.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

## ADVANTAGES

- Exceptional water savings: 85%
- Soft-touch operation
- Sleek lines
- Sleek design

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow mixer** - Ref. 794100

| | |
|---|---|
| Connector | F3/8" |
| Technology | Time flow |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms | ACS, BELGAQUA, WRAS, kiwa, DVGW |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |

