

SECURITHERM BIOCLIP

thermostatic sink mixer

Ref. H9611

Wall-mounted sequential thermostatic mixer








DESCRIPTION

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611





Wall-mounted SECURITHERM thermostatic sink mixer.
 Sequential thermostatic mixer: opens and closes with cold water.
 No risk of cross flow between hot and cold water.
 No non-return valves on the inlets.
 Wall-mounted mixer supplied with 2 removable stainless steel spouts L.136mm.
 Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant sequential thermostatic cartridge for sequential control of flow and temperature.
 Temperature can be adjusted from cold water up to 40°C, with temperature limiter set at 40°C.
 Thermal and chemical shocks are possible.
 Body and spout with smooth interiors and low water volume.
 Flow rate regulated at 7 lpm.
 Chrome-plated brass body.
 No manual contact thanks to Hygiene control lever L. 146mm.
 Mixer with 150mm centres supplied with offset STOP/CHECK connectors M1/2" M3/4" ideal for hospitals.
 Mixer ideal for healthcare facilities, retirement homes, hospitals and clinics.
 Sequential mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.


TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential mixer
Depth	201mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	

ADVANTAGES

-  Sequential: opens/closes with cold water
-  Hygiene: no non-return valves
-  Removable spout: reduces bacterial development
-  SECURITHERM: optimum anti-scalding safety



Repairability

