

# SECURITHERM BIOCLIP

## thermostatic sink mixer

Ref. H9611S

Wall-mounted sequential thermostatic mixer







### DESCRIPTION

**SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611S**





Wall-mounted SECURITHERM thermostatic sink mixer.  
 Sequential thermostatic mixer: opens and closes with cold water.  
 No risk of cross flow between hot and cold water.  
 No non-return valves on the inlets.  
 Wall-mounted mixer supplied with 2 removable stainless steel spouts L.136mm.  
 Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Scale-resistant sequential thermostatic cartridge for sequential control of flow and temperature.  
 Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C.  
 Thermal or chemical shocks are possible.  
 Body and spout with smooth interiors and low water volume.  
 Flow rate regulated at 7 lpm.  
 Chrome-plated brass body.  
 No manual contact thanks to Hygiene control lever L. 146mm.  
 Mixer with 150mm centres supplied with offset standard connectors M1/2" M3/4".  
 Mixer ideal for healthcare facilities, retirement homes, hospitals and clinics.  
 Sequential mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.


### ADVANTAGES

-  Sequential: opens/closes with cold water
-  Hygiene: no non-return valves
-  Removable spout: reduces bacterial development
-  SECURITHERM: optimum anti-scalding safety

### TECHNICAL CHARACTERISTICS

**SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611S**

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential mixer
Depth	195mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	  
Warranty	



Repairability

