SECURITHERM BIOCLIP thermostatic sink mixer

Ref. H9611S

Wall-mounted sequential thermostatic mixer

DESCRIPTION

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611S

Wall-mounted SECURITHERM thermostatic sink mixer.
Sequential thermostatic mixer: opens and closes with cold water.
No risk of cross flow between hot and cold water.
No non-return valves on the inlets.
Wall-mounted mixer supplied with 2 removable stainless steel spouts L.136mm.
Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant sequential thermostatic cartridge for sequential control of flow and temperature.
Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C.
Thermal or chemical shocks are possible.
Body and spout with smooth interiors and low water volume.
Flow rate regulated at 7 lpm.
Chrome-plated brass body.
No manual contact thanks to Hygiene control lever L. 146mm.
Mixer with 150mm centres supplied with offset standard connectors M1/2" M3/4".
Mixer ideal for healthcare facilities, retirement homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- Sequential: opens/closes with cold water
- Hygiene: no non-return valves
- Removable spout: reduces bacterial development
- SECURITHERM: optimum anti-scalding safety

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9611S

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential mixer
Depth	195mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY