

# Deck-mounted single hole mixer - 60 lpm

Ref. 5650T3

Swivelling spout H. 355mm L. 300mm

## DESCRIPTION

Deck-mounted single hole mixer - 60 lpm - Ref. 5650T3

Deck-mounted single hole catering mixer.  
Swivelling tubular spout H. 355mm L. 300mm with hygienic flow straightener.  
Ceramic cartridge Ø 45mm.  
Flow rate 60 lpm at 3 bar.  
Spout with smooth interior.  
Slimline control lever.  
Chrome-plated brass body and spout.  
Soldered copper pipe water inlets.  
Reinforced fixing.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

Deck-mounted single hole mixer - 60 lpm - Ref. 5650T3

|               |                                                                                         |
|---------------|-----------------------------------------------------------------------------------------|
| Connector     | Copper tails                                                                            |
| Drop height   | 355mm                                                                                   |
| Spout length  | 300mm                                                                                   |
| Flow rate     | 60 lpm                                                                                  |
| Finish        | Chrome-plated brass                                                                     |
| Norms         | ACS  |
| Warranty      |      |
| Repairability |      |



## ADVANTAGES



Rapid fill: flow rate 60 lpm at 3 bar



Body and spout suitable for professional use



Hygiene: spout with smooth interior



Reinforced fixing

