

# BLACK BINOPTIC electronic tap

Ref. 498035

Battery-operated, H. 250mm



## DESCRIPTION

**BLACK BINOPTIC electronic tap - Ref. 498035**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
Battery-operated with 123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
Matte black chrome finish.  
PEX flexible with filter and solenoid valve M $\frac{3}{8}$ ".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Drop height 250mm for countertop washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BLACK BINOPTIC electronic tap - Ref. 498035**

|               |                                                                                         |
|---------------|-----------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                            |
| Connector     | M3/8"                                                                                   |
| Technology    | Electronic                                                                              |
| Drop height   | 250mm                                                                                   |
| Spout length  | 185mm                                                                                   |
| Flow rate     | 3 lpm                                                                                   |
| Finish        | Matte black chrome                                                                      |
| Norms         | ACS  |
| Warranty      |      |
| Repairability |      |

## ADVANTAGES



90% water savings



Hygiene: no manual contact



LED diagnostic aid

