

TEMPOSTOP time flow tap 2 controls

Ref. 748210

Anti-blocking version (AB)




DESCRIPTION

TEMPOSTOP time flow tap 2 controls - [Ref. 748210](#)

Time flow basin tap for cross wall installation:
Time flow ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
2 controls: 1 button for mixed water and 1 button for cold water.
Tamperproof scale-resistant flow straightener.
Chrome-plated solid brass body M $\frac{1}{2}$ ".
Control \leq 200mm, spout \leq 230mm.
Ligature-resistant button is flush to wall.
Anti-rotating pin and back nut.
AB anti-blocking system: water will flow only when the push-button is released.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOSTOP time flow tap 2 controls - [Ref. 748210](#)

| | |
|--------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Time flow |
| Length | 200mm |
| Spout length | 75mm |
| Flow rate | 3 lpm |
| Norms | ACS |
| Warranty |  |

ADVANTAGES



Cross wall installation



Anti-blocking system



85% water savings



Maintenance outside area of use

