

TEMPOMATIC 4 electronic tap

Ref. 443536

Integrated batteries



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443536

Wall-mounted electronic basin tap:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless body L. 190mm
 Cap fixed in place by 2 concealed screws.
 Wall-mounted.
 Stopcock.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443536

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	190mm
Flow rate	3 lpm
Norms	   
Warranty	
Repairability	

ADVANTAGES



90% water savings



Hygiene: no manual contact



Integrated electronics



Replace batteries without removing tap

