

## TEMPOFLUX 1 direct flush kit

Ref. 761210

Time flow direct flush WC valve



### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761210

Flush system without cistern: directly connected to pipework.  
 For walls  $\leq 200\text{mm}$ .  
 Soft-touch operation.  
 Time flow  $\sim 7$  seconds.  
 Vacuum breaker.  
 Stopcock and flow rate/volume adjuster are integrated.  
 Chrome-plated metal body.  
 Inline inlet  $M\frac{3}{4}"$ .  
 Connection washer  $\varnothing 32/55\text{mm}$ .  
 Threaded rod can be cut to size.  
 Upstream supply pipes: minimum  $\varnothing 20\text{mm}$  required at all points (including connectors).  
 Base flow rate: 1 l/sec at 1 bar pressure.  
 With PVC flush tube  $\varnothing 32\text{mm}$ .  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 [Formerly ref: 761700]

### ADVANTAGES



No cistern: no stagnant water



Cross wall installation



Powerful flush is immediately available



Direct flush reduces the risk of leaks

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761210

|            |                                                                                     |
|------------|-------------------------------------------------------------------------------------|
| Connector  | $\frac{3}{4}"$                                                                      |
| Technology | Time flow                                                                           |
| Length     | 200mm                                                                               |
| Norms      |  |
| Warranty   |  |

