

TEMPOMATIC 5 electronic tap

Ref. 449001

Mains supply - plug-in





DESCRIPTION

TEMPOMATIC 5 electronic tap - Ref. 449001

Deck-mounted electronic basin tap:
230/6V recessed mains supply via plug.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body.
PEX flexible F3/8" with stopcock and filter.
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic tap - Ref. 449001

| | |
|--------------|---|
| Supply | 230/6V mains supply |
| Connector | F3/8" |
| Technology | Electronic |
| Drop height | 74mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Finish | Chrome-plated metal |
| Norms |  ACS |
| Warranty |  |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Mains supply via plug

