

BINOPTIC electronic basin tap

Ref. 370110

Mains supply, kit 2/2



DESCRIPTION

BINOPTIC electronic basin tap - Ref. 370110





Recessed electronic BINOPTIC 2 basin tap kit 2/2:
 Mains supply with 230/6V (cable and transformer supplied).
 Bright polished stainless steel plate 145 x 145mm with integrated electronics.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use.
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Anti-blocking security.
 Smooth interior spout with low volume of water (limits bacterial niches).
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with 370SBOX waterproof housing.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic basin tap - Ref. 370110

Connector	F½"
Technology	Electronic
Length	145mm
Width	145mm
Finish	Bright polished stainless steel
Norms	ACS
Warranty	30 YEAR WARRANTY

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Adjustable, modular waterproof housing
-  Concealed fixings

