

Electronic SECURITHERM shower mixer

Ref. 792452

Thermostatic electronic, kit 2/2



DESCRIPTION

Electronic SECURITHERM shower mixer - Ref. 792452

Recessed thermostatic electronic shower mixer, kit 2/2:
 Tamperproof satin stainless steel control plate 195 x 220mm.
 SECURITHERM thermostatic shower mixer ¾".
 Anti-scalding safety: automatic shut-off in the event of cold water failure.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.
 Battery-operated with CR-P2 223 6V Lithium battery.
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.
 Voluntary or automatic shut-off after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after last use).
 Flow rate 9 lpm at 3 bar.
 Concealed fixings, M½" stopcocks.
 Integrated non-return valves and filters.
 Chrome-plated Bayblend® control knob.
 Electronic shower mixer suitable for people with reduced mobility`.
 30-year warranty.
 Order with waterproof housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

Electronic SECURITHERM shower mixer - Ref. 792452

Supply	6V
Connector	½"
Technology	Électronique
Height	195mm
Depth	110mm
Width	220mm
Flow rate	9 lpm
Finish	Satin finish stainless steel
Norms	 ACS 
Warranty	

ADVANTAGES



Total hygiene: operate without manual contact



Anti-bacterial duty flush



Thermostatic temperature control



Instant shut-off if cold water supply fails

