SECURITHERM time flow shower mixer

Ref. 792218

Thermostatic time flow, kit 2/2



DESCRIPTION

SECURITHERM time flow shower mixer - Ref. 792218

Recessed thermostatic time flow shower mixer: Tamperproof satin finish stainless steel control plate 195 x 220mm. Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-scalding railsare: automatic shut-off if cold water rails.

Anti-cold showers function: automatic shut-off if hot water fails.

Temperature can be adjusted from 32 to 40°C, pre-set at 38°C.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate set at 9 lpm at 3 bar.

Concealed fixings, stopcocks M½".

Integrated non-return valves and filters.

Chrome-plated Bayblend® control knob.

Suitable for people with reduced mobility.

30-year warranty.

Order with recessed housing ref. 792BOX.

ADVANTAGES



Thermostatic temperature control



Instant shut-off if cold water supply fails



80% water savings



System tested to over 500,000 operations

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower mixer - Ref. 792218

Technology Time flow Height 195mm Depth 110mm Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS Warranty	Connector	1/2"
Depth 110mm Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS 1000 Warranty 3000	Technology	Time flow
Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS Warranty Warranty	Height	195mm
Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS TO THE PROPERTY TO THE PROPERT	Depth	110mm
Norms ACS Satin finish stainless steel Norms Warranty	Width	220mm
Norms ACS SELEAGUA Warranty	Flow rate	9 lpm
Warranty 30	Finish	Satin finish stainless steel
	Norms	
	Warranty	30 WARRANTY



