

# TEMPOMIX time flow shower mixer

Ref. 790218

Time flow single control, kit 2/2



## DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790218

Recessed time flow shower mixer kit 2/2:  
 Tamperproof bright polished stainless steel control plate 160 x 220mm.  
 TEMPOMIX 3/4" single control shower mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the control.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds, soft-touch operation.  
 Flow rate 12 lpm at 3 bar, can be adjusted.  
 Concealed fixings, stopcocks M1/2".  
 Chrome-plated metal control.  
 Integrated non-return valves and filters.  
 30-year warranty.  
 Order with recessed waterproof housing ref. 790BOX.

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790218

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector  | 1/2"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Technology | Time flow                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Height     | 160mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Depth      | 130mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Width      | 220mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Flow rate  | 12 lpm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Finish     | Bright polished stainless steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Norms      |    <br>    |
| Warranty   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## ADVANTAGES

-  80% water savings
-  Soft-touch operation
-  Installation recessed in wall
-  System tested to over 500,000 operations

