## **TEMPOFIX 3 frame system for urinals**

Ref. 543000D

Steel frame system for urinal with flexible, 1/2"



## **ADVANTAGES**



Easy and quick to install: supplied pre-mounted



Height and centres can be adjusted



Can be adjusted to wall thickness



230/6V mains supply

## **DESCRIPTION**

TEMPOFIX 3 frame system for urinals - Ref. 543000D

Steel frame system for urinal with flexible ½", kit ½:

Black powder-coated steel frame for wall-mounted installation.

Fixes to floor and load-bearing walls with anchoring bolts supplied.

Adjustable bracket from 95 - 280mm.

Frame height can be adjusted from 0 to 200mm.

Ø 50mm soil pipe with waterproof seal.

Tube with ½" brass connection for urinals with flexible inlet.

Delivered pre-mounted.

Compatible with solid wall finishes from 13 - 120mm.

Supplied with recessed housing.

Valve configured for system flush, with accessories and connection protection..


30-year warranty.


Order with control plate references 430000, 430010, 430020 or 430030.

## TECHNICAL CHARACTERISTICS

TEMPOFIX 3 frame system for urinals - Ref. 543000D

| Connector | 1⁄2"                      |
|-----------|---------------------------|
| Height    | 985 - 1,385mm             |
| Depth     | 160 - 220mm               |
| Width     | 430 mm                    |
| Finish    | Black powder-coated steel |
| Warranty  | 30 W                      |





© DELABIE