

Control plate for TEMPOMATIC 4 for urinals

Ref. 430030

Recessed electronic mains supply valve - For urinals



DESCRIPTION

Control plate for TEMPOMATIC 4 for urinals - Ref. 430030

TEMPOMATIC 4 electronic valve $F\frac{1}{2}$ ", kit 2/2.

Mains supply 230/6V.

Solenoid valve enables opening and closing of water.

Black wall plate 145 x 145mm in shock-resistant tempered glass with integrated electronics.

Shock-resistant infrared presence detection sensor.

Detection delay is 10 seconds.

3 programmes (rinsing volume can be adjusted according to urinal type).

High frequency mode (exclusive to DELABIE):

- Short rinse after each user.

- Additional rinse after the period of increased frequency of use.

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vaccums.

Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.

TEMPOMATIC 4 $F\frac{1}{2}$ " valve compatible with rain water.

Installation in waterproof housing with waterproof collar, transformer, filter and stopcock.

Suitable for people with reduced mobility.

30-year warranty.

Order with frame system references 543000 for urinals $\varnothing$ 35mm, 543000D for urinals with flexible $\frac{1}{2}$ " or with recessed housing 430SBOX.

TECHNICAL CHARACTERISTICS

Control plate for TEMPOMATIC 4 for urinals - Ref. 430030

Supply	230/6V mains supply
Technology	Electronic
Length	145mm
Width	145mm
Finish	Black wall plate in shock-resistant vitro-ceramic glass
Norms	   
Warranty	

ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high-frequency mode



Hygienic duty flush



Compatible with mains supply

