

TEMPOFLUX 3 control plate for WCs

Ref. 763040

Soft-touch operation time flow control, AB, recessed



DESCRIPTION

TEMPOFLUX 3 control plate for WCs - Ref. 763040

Control plate and recessed time flow direct flush valve TEMPOFLUX 3, kit 2/2: Flush system without cistern: directly connected to pipework. Chrome-plated metal plate 170x 170mm. Control plate is installed manually via hidden fixings. TEMPOFLUX 3 F $\frac{3}{4}$ " valve compatible with rain water. Soft-touch operation. AB anti-blocking system: flush only takes place once the push-button is released. 3L/9L dual flush can be adjusted to 2L/4L. Round design. Complies with European standard EN 12541 (class II acoustic level). Upstream supply pipes: minimum \varnothing 20mm required at all points (including connectors). Base flow rate: 1 L/sec at 1 bar dynamic pressure. Suitable for rimless WC pans and suitable for people with reduced mobility. 30-year warranty. Order with frame system reference 564065DE or 564060DE, or with 763BOX recessed housing.

ADVANTAGES

-  Soft-touch operation
-  Direct flush: no water stagnation
-  3L/9L dual flush
-  Maintenance made easy with front access

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 control plate for WCs - Ref. 763040

Connector	F $\frac{3}{4}$ "
Technology	Time flow
Height	170mm
Width	170mm
Finish	Chrome-plated metal
Norms	   
Warranty	

