TEMPOFLUX 3 control plate for WCs

Ref. 763040

Soft-touch operation time flow control, AB, recessed

DESCRIPTION

TEMPOFLUX 3 control plate for WCs - Ref. 763040

Control plate and recessed time flow direct flush valve TEMPOFLUX 3, kit 2/2:
Flush system without cistern: directly connected to pipework.
Chrome-plated metal plate 170x 170mm.
Control plate is installed manually via hidden fixings.
TEMPOFLUX 3 F¾" valve compatible with sea water, rain water and grey water.
Soft-touch operation.
AB anti-blocking system: flush only takes place once the push-button is released.
3L/6L dual flush can be adjusted to 2L/4L. Round design.
Complies with European standard EN 12541 (class II acoustic level).
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
Base flow rate: 1 L/sec at 1 bar dynamic pressure.
Suitable for rimless WC pans and suitable for people with reduced mobility.
30-year warranty.
Order with frame system reference 564065DE or 564060DE, or with 763BOX recessed housing.

ADVANTAGES

- Soft-touch operation
- Direct flush: no water stagnation
- 3L/6L dual flush
- Maintenance made easy with front access

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 control plate for WCs - Ref. 763040

Connector	F¾"
Technology	Time flow
Height	170mm
Width	170mm
Finish	Chrome-plated metal
Norms	
Warranty