

TEMPOFLUX 2 control plate for WCs

Ref. 578222

Soft-touch operation time flow valve, 3L/6L dual flush



DESCRIPTION

TEMPOFLUX 2 control plate for WCs - Ref. 578222

Control plate and TEMPOFLUX 2 time flow direct flush valve, kit 2/2: Flush system without cistern, directly connected to pipework.

Ø 195mm chrome-plated metal wall plate with concealed fixings.

3L/6L dual flush can be adjusted to 2L/4L.

Soft-touch operation.

Vacuum breaker.

Stopcock and flow rate/volume adjuster.

Solid brass body and shock-resistant, scale-resistant mechanism.

In-line inlet M $\frac{3}{4}$ ".

Compatible with rain water.

For walls 10 - 35mm.



Complies with European standard EN 12541 class II.

10-year warranty.

Order with frame system references 578305DE, 578300DE, 578405DE or 578400DE.

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 control plate for WCs - Ref. 578222

Connector	$\frac{3}{4}$ "
Technology	Time flow
Depth	Walls from 10 to 35mm
Flow rate	3L/6L or 2L/4L
Diameter	Ø 195mm
Finish	Chrome-plated metal
Norms	
Warranty	

ADVANTAGES



Soft-touch operation



Direct flush: no water stagnation



Flush is instantly available



3L/6L dual flush, can be adjusted to 2L/4L

