

# TEMPOFIX 3 wall-mounted frame system for WCs

Ref. 564000

For TEMPOMATIC mains supply flush valve - Ø 100mm

## DESCRIPTION

TEMPOFIX 3 wall-mounted frame system for WCs - Ref. 564000

Wall-mounted frame system for wall-hung WCs, kit 1/2:

Black powder-coated steel frame:

- For fixing to load-bearing walls.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Compatible with solid walls from 10 - 120mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- PVC soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions.

Recessed waterproof housing: flush system without cistern, directly connected to pipework.

- Compatible with TEMPOMATIC dual control or TEMPOMATIC Connect electronic WC valves.

- Compatible with 230/6V mains supply.

- Backflow prevention device inside the housing.

- Integrated stopcock and flow rate regulation.


Supplied pre-mounted.

30-year warranty.

Order with control plate references 464000, 464050, 465000 or 465050.

## TECHNICAL CHARACTERISTICS

TEMPOFIX 3 wall-mounted frame system for WCs - Ref. 564000

Connector	3/4"
Technology	Electronic and time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Diameter	Ø 100mm outlet
Finish	Black powder-coated steel
Warranty	



## ADVANTAGES



Quick and easy to install: delivered pre-mounted



Space-saving



Adapt to wall thickness



Compatible with mains supply

