

TEMPOFIX 3 self-supporting frame system for WCs

Ref. 564005

For dual control TEMPOMATIC electronic mains supply valve - Ø 100mm

DESCRIPTION

TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564005

Self-supporting frame system for wall-hung WCs, kit 1/2:

Black powder-coated steel frame:

- With large feet for fixing to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Compatible with solid walls from 10 - 120mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- ABS soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions.

Recessed waterproof housing: flush system without cistern, directly connected to pipework.

- Compatible with TEMPOMATIC dual control or TEMPOMATIC Connect electronic WC valve.

- Compatible with 230/6V mains supply.

- Backflow prevention device inside the housing.

- Integrated stopcock and flow rate regulation.

Supplied pre-mounted.

30-year warranty.

Order with control plate references 464000, 464050, 465000 or 465050.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564005

Connector	3/4"
Technology	Electronic and time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Diameter	Ø 100mm outlet
Finish	Black powder-coated steel
Norms	
Warranty	



ADVANTAGES



Quick and easy to install: delivered pre-mounted



Space-saving



Adapt to wall thickness



Compatible with mains supply

