
Wall-mounted TEMPOFIX 3 frame system for WCs

Ref. 578300BE

For TEMPOFLUX 2 time flow valve - Outlet Ø 90mm



DESCRIPTION

Wall-mounted TEMPOFIX 3 frame system for WCs - Ref. 578300BE

Wall-mounted frame system for wall-hung WCs, kit 1/2:
Black powder-coated steel frame:
- Fixes to load-bearing walls.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- For wall finishes from 10 to 35mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- ABS soil pipe, Ø 90mm HDPE outlet with waterproof seal, with 2 setting positions.

Fitted with a TEMPOFLUX 2 time flow direct flush:
- Flush system without cistern: directly connected to pipework.
- Vacuum breaker.
- Integrated stopcock and flow rate/volume adjuster.
- Solid brass body and shock-resistant, scale-resistant mechanism.
- In-line inlet M¾".
- Compatible with rain water.

Delivered pre-mounted.
30-year warranty.
Order with control plate references 578222, 578212 or 578230.

ADVANTAGES

- Quick and easy to install: delivered pre-mounted
- Space-saving
- Adapt to wall thickness
- Install behind wall

TECHNICAL CHARACTERISTICS

Wall-mounted TEMPOFIX 3 frame system for WCs - Ref. 578300BE

Connector	¾"
Technology	Time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Diameter	Ø 90mm outlet
Finish	Black powder-coated steel
Norms	
Warranty	30 YEAR WARRANTY

