

BIOFIL 2-month shower filter

Ref. 30261

Non-sterile



DESCRIPTION

BIOFIL 2-month shower filter - Ref. 30261

BIOFIL anti-Legionella and all-germ shower filter.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Qualified water volume per duration of use: 6,000 litres.

Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).

Non-sterile filter.

CE Class I medical device.

Weight: empty filter 105g / filled filter 186g.

Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

ADVANTAGES



Anti-Legionella and all-germ



Space saving



Lifespan: 2 months after installation




Quick to install without tools

TECHNICAL CHARACTERISTICS

BIOFIL 2-month shower filter - Ref. 30261

Connector	M1/2"
Technology	Point-of-use filtration
Height	62mm
Length	194mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	2 months



Norms

ACS

WRAS

**KTW
BWGL**

CE

