BIOFIL 2 month shower filter

Ref. 20261

Sterile

DESCRIPTION

BIOFIL 2 month shower filter - Ref. 20261

BIOFIL anti-Legionella and all-germ shower head filter.
Device material: ABS
Type of membrane: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 6,000 litres.
Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
Sterile filter. Individually wrapped, sterile.
CE Class Is medical device.
Weight: empty filter 105g / full filter 186g.
Single reference. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Lifespan: 2 months after installation
- Easy to install without tools

TECHNICAL CHARACTERISTICS

BIOFIL 2 month shower filter - Ref. 20261

Connector	M1/2"
Technology	Filtration terminale
Height	62mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	2 months
Norms	ACS WRAS KTW BWGL CE