

BIOFIL 2 month shower filter

Ref. 20261

Sterile








DESCRIPTION

BIOFIL 2 month shower filter - Ref. 20261

BIOFIL anti-Legionella and all-germ shower head filter.
 Device material: ABS
 Type of membrane: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Qualified water volume per duration of use: 6,000 litres.
 Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 2 months after installation.
 Resistance to thermal shocks: 70°C for 30 minutes.
 Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
 Sterile filter. Individually wrapped, sterile.
 CE Class Is medical device.
 Weight: empty filter 105g / full filter 186g.
 Single reference. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 2 month shower filter - Ref. 20261

Connector	M1/2"
Technology	Filtration terminale
Height	62mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	2 months
Norms	    

ADVANTAGES

-  Anti-Legionella and all-germ
-  Space saving
-  Lifespan: 2 months after installation
-  Easy to install without tools

