

TEMPOMATIC MIX 5

electronic basin mixer

Ref. 49900015

Mains supply - recessed unit



DESCRIPTION

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900015

Deck-mounted electronic basin mixer:
 230/6V recessed mains supply.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated metal body.
 PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-return valves and conical inlets Ø 15.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900015

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	ACS  WRAS
Warranty	



ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated electronics and solenoid valve
-  Recessed mains supply

