

## TEMPOMATIC MIX 5 electronic basin mixer

Ref. 49900115

Mains supply - plug-in



### DESCRIPTION

**TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900115**

Deck-mounted electronic basin mixer:  
230/6V recessed mains supply via plug.  
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Duty flush (~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated metal body.  
PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-return valves and conical inlets  $\varnothing$  15.  
Fixing reinforced by two stainless steel rods.  
Anti-blocking security.  
Side temperature control with adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**TEMPOMATIC MIX 5 electronic basin mixer - Ref. 49900115**

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " $\varnothing$ 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	 ACS  WRAS
Warranty	 30 YEAR WARRANTY

### ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Integrated electronics and solenoid valve



Mains supply via plug

