

TEMPOMATIC 5 electronic basin tap

Ref. 44900015

Mains supply







DESCRIPTION

TEMPOMATIC 5 electronic basin tap - Ref. 44900015





Basin-mounted electronic tap:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body.
PEX flexibles M $\frac{1}{2}$ " with stopcocks, filters, non-return valves and conical inlets Ø 15mm.
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 44900015

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	  
Warranty	

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Integrated solenoid valve
-  Recessed mains supply

