

Shower kit with SECURITHERM thermostatic mixer

Ref. H9768SKIT

Shower riser rail with H9768S thermostatic shower mixer



DESCRIPTION

Shower kit with SECURITHERM thermostatic mixer - Ref. H9768SKIT

Shower riser rail with thermostatic dual control mixer.
Shower kit with SECURITHERM thermostatic shower mixer.
Thermostatic mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic cartridge adjusts the temperature.
1/4-turn ceramic valve head adjusts the flow rate.
Temperature control up to 43°C.
Double temperature limiter: 1st limiter set at 41°C, 2nd limiter set at 43°C.
Thermal shocks are possible without removing the control knob or shutting off the cold water.
Flow rate limited to 9 lpm at 3 bar.
Body made from chrome-plated brass, and with ERGO control knobs.
M1/2" bottom outlet.
Filters integrated in the inlets, F3/4".
Mixer with offset standard wall connectors, M1/2" M3/4".

- Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).
- Shower head retaining collar (ref. 830).

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
Shower kit with 30-year warranty.

TECHNICAL CHARACTERISTICS

Shower kit with SECURITHERM thermostatic mixer - Ref. H9768SKIT

Technology	SECURITHERM thermostatic shower mixer with no non-return valves
Depth	84mm
Width	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS
Warranty	

ADVANTAGES



Total hygiene: mixer with no non-return valves



SECURITHERM: optimised anti-scalding safety



Thermostatic: total temperature stability



Securitouch: thermal insulation prevents burns

