

TEMPOFLUX 3 AB flush kit

Ref. 763266

Anti-blocking direct flush WC kit



DESCRIPTION

TEMPOFLUX 3 AB flush kit - Ref. 763266

Flush system without cistern: directly connected to pipework.
 For walls ≤ 200 mm.
 Soft-touch operation.
 AB anti-blocking system: flush only takes place once the push-button is released.
 Time flow ~ 7 seconds.
 Vacuum breaker.
 Stopcock and volume/flow rate adjustment, activation unit and cartridge are all integrated and accessible via the service duct.
 Chrome-plated metal push-button.
 Shock-resistant mechanism.
 In-line inlet M $\frac{3}{4}$ ".
 Complies with European standard EN 12541 (class II acoustic level).
 Cut-to-size threaded rod.
 Upstream supply pipes: minimum $\varnothing 20$ mm required at all points (including connectors).
 Base flow rate: 1L/sec at 1 bar dynamic pressure.
 With $\varnothing 32$ mm PVC flush tube.
 Compatible with rain water.
 Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES



Anti-blocking system



Cross wall installation



Flush is powerful and instantly available



Direct flush: limits the risk of leaks

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 AB flush kit - Ref. 763266

Connector	$\frac{3}{4}$ "
Technology	Time flow
Norms	 
Warranty	

