

## TEMPOFLUX 3 AB flush kit

Ref. 763266

Anti-blocking direct flush WC kit

### DESCRIPTION

TEMPOFLUX 3 AB flush kit - Ref. 763266

Flush system without cistern: directly connected to pipework.

For walls  $\leq 200\text{mm}$ .

Soft-touch operation.

AB anti-blocking system: flush only takes place once the push-button is released.

Time flow  $\sim 7$  seconds.

Vacuum breaker.

Stopcock and volume/flow rate adjustment, activation unit and cartridge are all integrated and accessible via the service duct.

Chrome-plated metal push-button.

Shock-resistant mechanism.

In-line inlet  $M\frac{3}{4}"$ .

Complies with European standard EN 12541 (class II acoustic level).

Cut-to-size threaded rod.

Upstream supply pipes: minimum  $\varnothing 20\text{mm}$  required at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure.

With  $\varnothing 32\text{mm}$  PVC flush tube.


Compatible with rain water.

Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 AB flush kit - Ref. 763266

Connector	$\frac{3}{4}"$
Technology	Time flow
Warranty	



### ADVANTAGES



Anti-blocking system



Cross wall installation



Flush is powerful and instantly available



Direct flush: limits the risk of leaks

