Self-supporting fire retardant TEMPOFIX 3 frame system for WCs

Ref. 565065

For TEMPOFLUX 3



DESCRIPTION

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

Self-supporting frame system for wall hung WCs, kit 1/2
Fire retardant CF 60 min - EI60.
Black powder-coated steel frame with large feet for load-bearing floors:
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer and intumescent collar for fire protection.
- ABS soil pipe, Ø 100mm outlet to glue to waterproof seal, with 2 setting positions and intumescent collar for fire protection.
- Compatible with solid walls from 53 to 105mm (4 BA13 and tiles minimum).
Recessed waterproof housing with intumescent collar and fire protection set:
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate regulation.
Supplied premounted.
30-year warranty.
Order with control plate reference 763000.

ADVANTAGES

- Fire retardant 60 minutes
- Quick and easy to install: delivered pre-mounted
- Space saving
- Adapt to wall thickness

TECHNICAL CHARACTERISTICS

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065

Connector	F¾"
Technology	Time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Finish	Black powder-coated steel
Norms	
Warranty	30 YEAR WARRANTY

