

# Recessed thermostatic sequential shower mixer

Ref. H9631

SECURITHERM mixer with no non-return valves, kit 2/2



## DESCRIPTION

Recessed thermostatic sequential shower mixer - Ref. H9631

Recessed thermostatic shower mixer, kit 2/2 :  
Thermostatic sequential shower mixer: opens/closes with cold water.  
Mixer with no non-return valves on the inlets (reduces bacterial development).  
No risk of cross flow between the hot and cold water.  
Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.  
Prevents cold showers: shuts off immediately if hot water supply fails.  
Securitouch thermal insulation prevents burns.  
Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature.  
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.  
Thermal shocks are possible.  
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.  
ERGO controls.  
M $\frac{3}{4}$ " inlets with integrated filters.  
Order a wall-mounted outlet or shower head to complete.  
Bright polished stainless steel cover plate 166 x 166mm.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Sequential mixer ideal for people with reduced mobility.  
Shower mixer with 30-year warranty.  
Order with waterproof recessing housing ref. H96BOX.

## ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: total temperature stability

## TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer - Ref. H9631

|                     |                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------|
| Technology          | SECURITHERM Securitouch thermostatic sequential shower mixer                            |
| Flow rate           | Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head              |
| Temperature limiter | Yes                                                                                     |
| Finish              | Chrome-plated brass                                                                     |
| Norms               | ACS  |
| Warranty            |      |
| Repairability       |      |

