TEMPOMIX 3 AB time flow mixer

Ref. 794000AB

Soft-touch operation, stopcocks, AB system



TEMPOMIX 3 AB time flow mixer - Ref. 794000AB

Deck-mounted single control time flow basin mixer:

Soft-touch operation.

Temperature control and operation on the push-button.

Time flow ~7 seconds.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Tamperproof scale-resistant flow straightener.

Chrome-plated metal body.

PEX flexibles F3/8" with stopcocks, filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Adjustable maximum temperature limiter.

AB anti-blocking system: water will flow only when the push-button is released.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 AB time flow mixer - Ref. 794000AB

Connector	F%"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	B ACS
Warranty	30 WASRANTY



ADVANTAGES



Exceptional water savings: 85%




Anti-blocking system



Soft-touch operation



Sleek design



© DELABIE https://www.delabie.com