TEMPOMIX 3 AB time flow mixer

Ref. 794100AB

Soft-touch operation, AB system

DESCRIPTION

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated solid brass body.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Adjustable maximum temperature limiter.
AB anti-blocking system: water will flow only when the push-button is released.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 85%
- Anti-blocking system
- Soft-touch operation
- Sleek design

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 AB time flow mixer - Ref. 794100AB

Connector	F⅜"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	BELGAQUA ACS
Warranty	30 YEAR WARRANTY