

# Recessed mechanical mixer with angled outlet

Ref. 2551

Mechanical mixer in a waterproof housing, kit 2/2



## DESCRIPTION

### Recessed mechanical mixer with angled outlet - Ref. 2551

Mechanical shower mixer which can be recessed; with angled outlet, kit 2/2. Single control mixer with Ø 40mm standard ceramic cartridge. Pre-set maximum temperature limiter. No risk of cross flow between the hot and cold water. No non-return valves on the inlets. Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water. Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head. Solid control lever. Order a shower head to complete. Bright polished stainless steel cover plate 166 x 166mm with wall-mounted angled outlet. Mechanical shower mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Shower mixer suitable for people with reduced mobility. Mixer with 30-year warranty. Order with a waterproof recessing housing ref. 254CBOX.

## TECHNICAL CHARACTERISTICS

### Recessed mechanical mixer with angled outlet - Ref. 2551

Supply	1/2"
Length	166mm
Width	166mm
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms **ACS** **WRAS** **B**

Warranty **30 YEAR WARRANTY**

Repairability **50 YEARS REPAIRABILITY**

## ADVANTAGES



Thermal shock without removing the control lever



100% waterproof: angled outlet on the wall plate



Ergonomic: solid lever is easy to grip



Safety: maximum temperature limiter

