

## TEMPOMATIC 4 electronic tap

Ref. 44000615CO

Integrated batteries, stopcock Ø 15mm




### DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000615CO

Deck-mounted electronic basin tap:  
 Battery-operated with integrated CR123 6V Lithium batteries.  
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Active, infrared presence detection, sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body.  
 Cap fixed in place by two concealed screws.  
 Copper tails with stopcock, filter and Ø 15mm conical inlet.  
 Fixing reinforced by two stainless steel rods.  
 Anti-blocking security.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000615CO

|              |   |
|--------------|---|
| Supply       | 6V batteries  |
| Connector    | M½" Ø 15mm  |
| Technology   | Electronic  |
| Drop height  | 70mm  |
| Spout length | 105mm   |
| Flow rate    | 3 lpm   |
| Warranty     |  |

### ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated in tap body



Anti-bacterial proliferation duty flush