BINOPTIC 2 electronic tap

Ref. 375130

Mains, deck-mounted, H. 250mm



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 375130

Deck-mounted chrome-plated matte black electronic basin tap: 230/6V mains supply.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use). Stainless steel tap, 250mm high for countertop basins.

Presence detection sensor at the end of the spout optimises detection. PEX flexible with filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth interior spout with low water volume (limits bacterial niches). Set detection distance, duty flush and launch duty flush by hand. Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush




LED diagnostic aids

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 375130

Supply	230/6V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Norms	ACS
Warranty	30 g



© DELABIE https://www.delabie.com