Recessed thermostatic sequential shower mixer with angled outlet

Ref. H9633L

SECURITHERM mixer with no non-return valves, kit 2/2

DESCRIPTION

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

Recessed thermostatic shower with elbow outlet, kit 2/2 :
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: cold water supply shuts off if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and temperature.
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.
Hygiene lever L. 100mm.
Filters integrated on the inlets M3/4".
Bright polished stainless steel wall plate 166 x 166mm.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Shower mixer with 30-year warranty.
Order the waterproof recessing housing ref. H96CBOX.

ADVANTAGES

- Sequential: opens/closes with cold water
- Maximum hygiene: no non-return valves
- SECURITHERM: optimal anti-scalding safety
- Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

Technology	SECURITHERM Securitouch thermostatic sequential mixer
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY