

Recessed thermostatic sequential shower mixer

Ref. H9631L

SECURITHERM mixer with no non-return valves, kit 2/2



DESCRIPTION

Recessed thermostatic sequential shower mixer - Ref. H9631L

Recessed Securitherm thermostatic shower, kit 2/2 :
 Thermostatic sequential mixer: opens and closes with cold water.
 Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
 No risk of cross flow between hot and cold water.
 Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
 Prevents cold showers: cold water supply shuts off if hot water supply fails.
 Sequential mixer with Securitouch thermal insulation prevents burns.
 Scale-resistant thermostatic sequential cartridge adjusts the flow rate and temperature.
 Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
 Tested without water to comply with NHS requirements. No pre-set temperature.
 Thermal shocks are possible.
 Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.
 Hygiene lever L. 100mm.
 Filters integrated on the inlets M3/4".
 Order a shower head to complete.
 Bright polished stainless steel wall plate 166 x 166mm.
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Sequential mixer suitable for people with reduced mobility.
 Shower mixer with 30-year warranty.
 Order the waterproof recessing housing ref. H96BOX.

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety




Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer - Ref. H9631L

| | |
|---------------------|--|
| Technology | SECURITHERM Securitouch thermostatic sequential mixer |
| Height | 166mm |
| Width | 166mm |
| Flow rate | Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |



Norms



Warranty



Repairability

