BIOFIL 4-month shower head filter

Ref. 20461

Sterile



DESCRIPTION

BIOFIL 4-month shower head filter - Ref. 20461

DELABIE anti-Legionella and all-germ shower filter.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 12,000 litres.
Filtration flow rate: 6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.1 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 4 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).
Sterile filter.
Weight: empty filter 133g / full filter 259g.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.

ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Lifespan: 4 months after installation
- Easy to install without tools

TECHNICAL CHARACTERISTICS

BIOFIL 4-month shower head filter - Ref. 20461

Connector	M1/2"
Technology	Point-of-use filtration
Height	77mm
Length	194mm
Flow rate	6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.1 at 5 bar
Diameter	56mm
Lifespan	4 months
Norms	ACS WRAS KTW BWGL CE

