

BIOFIL 2 month spout filter

Ref. 30040

Non-sterile



DESCRIPTION

BIOFIL 2 month spout filter - Ref. 30040




Single use removable BIOFIL anti-Legionella and all-germ spout.
 Can be installed instead of removable BIOCLIP spouts (no need for any tools or to shut off the water supply).
 Membrane type: tubular microfiltration.
 Membrane material: Polyethylene.
 Pore cut-off threshold: 0.1µm nominal-rated, sterilising grade.
 Qualified water volume per duration of use: 6,000 litres.
 Filtration surface area 1,200cm².
 Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the mixer/tap).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 2 months after installation.
 Compatible with and resistant to thermal and chemical shocks.
 Non-sterile filter.
 Weight: 40g.
 Reference for a single unit. Must be ordered in multiples of 10.
 Packaged in boxes of 10 units.

ADVANTAGES

-  Anti-Legionella and all-germ
-  Easy to install without tools
-  Lifespan: 2 months after installation
-  Maintains drop height

TECHNICAL CHARACTERISTICS

BIOFIL 2 month spout filter - Ref. 30040

| | |
|------------|---|
| Technology | Point-of-use filtration |
| Length | 138mm |
| Flow rate | 6 lpm at 3 bar |
| Norms | ACS    |

