

# BIOFIL 2 month spout filter

Ref. 30040

Non-sterile



## DESCRIPTION

**BIOFIL 2 month spout filter - Ref. 30040**

Single use removable BIOFIL anti-Legionella and all-germ spout.  
Can be installed instead of removable BIOCLIP spouts (no need for any tools or to shut off the water supply).

Membrane type: tubular microfiltration.

Membrane material: Polyethylene.

Pore cut-off threshold: 0.1µm nominal-rated, sterilising grade.

Qualified water volume per duration of use: 6,000 litres.

Filtration surface area 1,200cm<sup>2</sup>.

Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the mixer/tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Compatible with and resistant to thermal and chemical shocks.

Non-sterile filter.

Weight: 40g.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

## ADVANTAGES



Anti-Legionella and all-germ



Easy to install without tools



Lifespan: 2 months after installation



Maintains drop height

## TECHNICAL CHARACTERISTICS

**BIOFIL 2 month spout filter - Ref. 30040**

Technology	Point-of-use filtration
Length	138mm
Flow rate	6 lpm at 3 bar
Norms	   

