

# BINOPTIC MIX 2 electronic basin mixer

Ref. 484010E

Mains, recessed, stopcocks, L. 240mm, Bluetooth®




## DESCRIPTION

**BINOPTIC MIX 2 electronic basin mixer - Ref. 484010E**

Recessed chrome-plated electronic basin mixer:  
 230/6V mains supply.  
 Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the mixer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant aerator.  
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
 Wall-mounted stainless steel mixer.  
 Presence detection sensor at the end of the spout optimises detection.  
 Anti-blocking security.  
 Spout with smooth interior and low water volume (reduces bacterial development).  
 Side temperature control with adjustable maximum temperature limiter on mixers.  
 Set detection distance, duty flush and launch thermal shocks manually.  
 Bluetooth® version: advanced settings and operating data download via DELABIE Connect app.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX 2 electronic basin mixer - Ref. 484010E**

|              |   |
|--------------|---|
| Supply       | 230/6V mains supply   |
| Connector    | M $\frac{1}{2}$ "   |
| Technology   | Electronic  |
| Spout length | 240mm   |
| Flow rate    | 3 lpm   |
| Finish       | Chrome-plated   |
| Warranty     |  |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



Easy to configure & monitor operation

