BINOPTIC MIX 2 electronic basin mixer

Ref. 47503015

Mains, deck-mounted, H. 250mm

DESCRIPTION

BINOPTIC MIX 2 electronic basin mixer - Ref. 47503015

Deck-mounted chrome-plated matte black electronic basin mixer:
230/6V mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (~60 seconds every 24 hours after the last use).
Stainless steel mixer, 250mm high for countertop basins.
Active, infrared presence detection, sensor at the end of the spout optimises detection.
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Smooth interior spout with low water volume (limits bacterial niches).
Side temperature control with adjustable maximum temperature limiter.
Set duty flush and launch thermal shocks manually.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Total hygiene: no manual contact
- 90% water savings
- Anti-bacterial proliferation duty flush
- Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 47503015

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	250mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Warranty	30 YEAR WARRANTY