

# TEMPOMIX 3 time flow basin mixer

Ref. 794120

Soft-touch operation, deck-mounted, H.250

## DESCRIPTION

**TEMPOMIX 3 time flow basin mixer - Ref. 794120**

Deck-mounted single control time flow basin mixer:  
Soft-touch operation.  
Temperature control and operation on the push-button.  
Time flow pre-set at ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated stainless steel body, 250mm height for deck-mounting.  
F3/8" PEX flexibles with filters and non-return valves.  
Fixing reinforced by back-nut.  
Adjustable maximum temperature limiter.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMIX 3 time flow basin mixer - Ref. 794120**

|             |                                                                                                                                                                                    |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector   | F3/8"                                                                                                                                                                              |
| Technology  | Time flow                                                                                                                                                                          |
| Drop height | 250mm                                                                                                                                                                              |
| Flow rate   | 3 lpm                                                                                                                                                                              |
| Finish      | Chrome                                                                                                                                                                             |
| Norms       |   <b>ACS</b> |
| Warranty    |                                                                                                 |



## ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Reinforced fixings with back-nut



Sleek design

