

SPORTING 2 SECURITHERM AB

time flow shower panel

Ref. 714732AB

Thermostatic, AB system, scale-resistant nozzle


DESCRIPTION

SPORTING 2 SECURITHERM AB time flow shower panel - Ref. 714732AB

Thermostatic time flow shower panel:
 Anodised aluminium and chrome-plated satin finish panel.
 Slimline structure with concealed fixings.
 Soft-touch operation.
 Automatic mechanical flush with each use.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.
 Accessible filters and non-return valves.
 Integrated stopcocks.
 AB anti-blocking system: water will flow only when the push-button is released.
 M $\frac{1}{2}$ " connection.
 Suitable for people with reduced mobility.
 30-year warranty.
 SECURITHERM technology:
 Thermostatic shower mixer directly integrated in the head of the shower panel.
 Temperature set by the installer.
 Stable temperature, pre-set at 38°C.
 Anti-scalding failsafe: automatic shut-off if the cold water fails.
 Anti-cold showers function: automatic shut-off if the hot water fails.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM AB time flow shower panel - Ref. 714732AB

Connector	M1/2"
Technology	Time flow
Height	1020mm
Depth	16mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Warranty	



ADVANTAGES



80% water savings



Automatic shut-off if cold water fails



Soft-touch operation



Sleek lines, concealed fixings

